

PROPRIETES TECHNIQUES

SYNTIUM 5000 XS

CODE DU PRODUIT: 1814

EMPLOI

Syntium 5000 XS is formulated for the latest generation of gasoline and diesel powered engines complying to Euro 4 & 5 emission standards.

Syntium 5000 XS has been specifically designed to help prolong the life and maintain the efficiency of emission systems in both diesel and gasoline passenger car vehicles.

Syntium 5000 XS is particularly suitable for diesel passenger car vehicles fitted with particulate filters such as BMW, Mercedes Benz etc...

Syntium 5000 XS is also suitable for engines requiring GM/OPEL dexos 2 and will also cover the older GM LL-A-025 and GM LL-B-025 requirements.

SPECIFICATION

SAE 5W-30, API SN/CF, BMW LL-04, ACEA C3, Approbation MB 229.51, VW 505.01

TEST

DESCRIPTION DU TEST	METHODE	UNITE DE MESURE	VALEUR TYPIQUE
ASPECT	--	--	B. & C.
DENSITE A 15°C	ASTM D 4052	g/cm ³	0,850
VISCOSITA' @ 100°C	ASTM D 445	cSt	11,6
INDICE DE VISCOSITE	ASTM D 2270	--	165
T.B.N.	ASTM D 2896	mg KOH/g	8,1
POINT D'ÉCLAIR DE CLEVELAND (CUVETTE OUVERTE)	ASTM D 92	°C	> 200
POINT D'ECOULEMENT	ASTM D 97	°C	< -36
MOUSSE A 24°C	ASTM D 892	cc/s	TRACES/0

Les données présentes dans cette fiche de sécurité ne constituent pas une spécification et elles sont soumises aux tolérances normales de production.