

## PROPRIETES TECHNIQUES

### SYNTIUM 1000

CODE DU PRODUIT: 1816

#### EMPLOI

SYNTIUM 1000 is formulated for the most recent gasoline and diesel engines not equipped with diesel particulate filters. This product is also suitable for older gasoline and diesel powered vehicles especially where the car manufacturer requires ACEA A3/B4 or A3/B3 level of performance.

SYNTIUM 1000 is suitable for Renault non-turbo gasoline engines requiring Renault RN0700 level of performance.

SYNTIUM 1000 will cover PSA gasoline and diesel powered engines that require B71 2300, ACEA A3/B4 level and B71 2295 ACEA A3/B3 level of performance but excluding diesel engines fitted with the PSA diesel particulate filter system (FAP).

#### SPECIFICATION

SAE 10W-40, API SN/CF, ACEA A3/B4, Approbation MB 229.1, VW 501.01-505.00,  
RENAULT RN0700

#### TEST

DESCRIPTION DU TEST	METHODE	UNITE DE MESURE	VALEUR TYPIQUE
ASPECT	--	--	B. & C.
DENSITE A 15°C	ASTM D 4052	g/cm <sup>3</sup>	0,875
VISCOSITA' @ 100°C	ASTM D 445	cSt	14,2
INDICE DE VISCOSITE	ASTM D 2270	--	150
T.B.N.	ASTM D 2896	mg KOH/g	10,0
POINT D'ÉCLAIR DE CLEVELAND (CUVETTE OUVERTE)	ASTM D 92	°C	> 200
POINT D'ECOULEMENT	ASTM D 97	°C	< -30
MOUSSE A 24°C	ASTM D 892	cc/s	TRACES/0

Les données présentes dans cette fiche de sécurité ne constituent pas une spécification et elles sont soumises aux tolérances normales de production.