


DONNEES TECHNIQUES

Alternator Charge Current [A]	120
Vehicle Main Current	for vehicles with 12V main current
Type de poulie	PVR5
Clamp	M5 B+
Plug Type ID	PLUG386

PHOTOS




Bornes	
B+	Positive
D+	Trio (Lamp)
DF	Field (B)

DOCUMENTS

BT-130 Refus des carcasses alternateurs/démarrateurs

APPLICATIONS

AUDI		
A4 (94-01) (8D2, B5) - 1.9 Di	75 ch	12.1995 > 11.2000
A4 (94-01) (8D2, B5) - 1.9 TDI	90 ch	01.1995 > 11.2000
	110 ch	10.1995 > 11.2000
A4 (94-01) (8D2, B5) - 1.9 TDI quattro	110 ch	09.1996 > 11.2000
A4 (94-01) Avant (8D5, B5) - 1.9 Di	75 ch	03.1996 > 09.2001
A4 (94-01) Avant (8D5, B5) - 1.9 TDI	90 ch	02.1996 > 09.2001
	110 ch	02.1996 > 09.2001
A4 (94-01) Avant (8D5, B5) - 1.9 TDI quattro	110 ch	09.1996 > 09.2001
A6 (97-04) (4B, C5) - 1.9 TDI	110 ch	04.1997 > 10.2000
A6 (97-04) Avant (4B, C5) - 1.9 TDI	110 ch	02.1998 > 04.2001
VOLKSWAGEN		
PASSAT (96-00) (3B2) - 1.9 TDI	90 ch	10.1996 > 11.2000
PASSAT (96-00) Variant (3B5) - 1.9 TDI	90 ch	06.1997 > 11.2000

 Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.