


DONNEES TECHNIQUES

Alternator Charge Current [A]	70
Vehicle Main Current	for vehicles with 12V main current
Type de poulie	SANS
Pulleys	without belt pulley
Terminal/Clamp	with revcounter coupling
Clamp	M6 B+
Plug Type ID	PLUG384

PHOTOS




Bornes	
B+	Positive
D+	Trio (Lamp)
W	Revolution meter

DOCUMENTS

BT-130 Refus des carcasses alternateurs/démarrateurs

APPLICATIONS

FORD		
ESCORT (80-86) (GAA) - 1.6 D	54 ch	02.1984 > 12.1985
ESCORT (80-86) Break (AWA) - 1.6 D	54 ch	02.1984 > 12.1985
ESCORT (80-86) Cabriolet (ALD) - 1.3	69 ch	09.1983 > 12.1985
ESCORT (86-90) (GAF, AWF, ABFT) - 1.3	69 ch	11.1986 > 07.1988
ESCORT (86-90) (GAF, AWF, ABFT) - 1.6 D	54 ch	01.1986 > 01.1989
ESCORT (86-90) Break (AWF, AVF) - 1.3	69 ch	11.1986 > 07.1988
ESCORT (86-90) Break (AWF, AVF) - 1.6 D	54 ch	01.1986 > 01.1989
FIESTA (83-89) (FBD) - 1.4 (FBD)	71 ch	10.1986 > 02.1989
	73 ch	02.1987 > 02.1989
FIESTA (89-97) (GFJ) - 1.4	73 ch	03.1989 > 12.1995
FIESTA (89-97) (GFJ) - 1.6	88 ch	01.1989 > 01.1994
FIESTA (89-97) (GFJ) - 1.6 XR2i	103 ch	03.1989 > 03.1993
	110 ch	03.1989 > 01.1994

 Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.