


DONNEES TECHNIQUES

Compressed length [mm]	600
Uncompressed length [mm]	625
Number of splines (wheels side)	25
	for vehicles without ABS
(wheels side) shoulder Ø [mm]	57
(wheels side) CV Joint Ø [mm]	90
Number of splines (gearbox side)	24
(gearbox side) CV Joint Ø [mm]	81
(gearbox side) shoulder Ø [mm]	40

PHOTOS




DOCUMENTS

BT-100	Conseils de montage des cardans
BT-104	Soufflets et Triaxes FIAT
BT-105	Soufflets et Triaxes SEAT
BT-131	Refus des carcasses transmissions

APPLICATIONS

PEUGEOT		
306 3 volumes (7B, N3, N5) - 1.9 SRDT	90 ch	06.1994 > 05.2001
306 3 volumes (7B, N3, N5) - 2.0	132 ch	03.1997 > 05.2001
306 3 volumes (7B, N3, N5) - 2.0 HDI 90	90 ch	06.1999 > 05.2001
306 3 volumes (7B, N3, N5) - 2.0 S16	150 ch	06.1994 > 05.2001
	152 ch	06.1994 > 05.2001
306 3/5 portes (7A, 7C, N3, N5) - 1.9 DT	90 ch	05.1993 > 05.2001
306 3/5 portes (7A, 7C, N3, N5) - 2.0 HDI 90	90 ch	06.1999 > 05.2001
306 3/5 portes (7A, 7C, N3, N5) - 2.0 S16	150 ch	06.1994 > 05.2001
	152 ch	05.1993 > 05.2001
	163 ch	03.1996 > 05.2001
306 Break (7E, N3, N5) - 1.9 TD	90 ch	02.1997 > 04.2002
306 Break (7E, N3, N5) - 2.0	132 ch	03.1997 > 04.2002
306 Break (7E, N3, N5) - 2.0 HDI 90	90 ch	06.1999 > 04.2002
306 Cabriolet (7D, N3, N5) - 2.0	121 ch	03.1994 > 04.2002
405 (92-96) (4B) - 1.9 TD	90 ch	08.1992 > 10.1995

PEUGEOT		
405 (92-96) (4B) - 2.0	121 ch	08.1992 > 10.1995
405 (92-96) (4B) - 2.0 X4	121 ch	08.1992 > 10.1995
405 (92-96) (4B) - 2.0 16V	150 ch	06.1994 > 10.1995
405 (92-96) (4B) - 2.0 MI-16	152 ch	08.1992 > 10.1995
405 (92-96) (4B) - 2.0 T 16 X4	196 ch	08.1992 > 10.1995
405 (92-96) Break (4E) - 1.9 TD	90 ch	08.1992 > 10.1996
405 (92-96) Break (4E) - 2.0	121 ch	08.1992 > 10.1996
405 (92-96) Break (4E) - 2.0 4x4	121 ch	08.1992 > 10.1996

 Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.