

DONNEES TECHNIQUES

Length [mm]	750
Number of splines (wheels side)	21
Number of Teeth, ABS ring	44
	for vehicles with ABS
ABS Ring Ø [mm]	85
ABS ring type	R
(wheels side) CV Joint Ø [mm]	86
Number of splines (gearbox side)	23
(gearbox side) CV Joint Ø [mm]	72
	With mounting pin (gearbox side)
	ABS ring 8mm wide

PHOTOS




DOCUMENTS

BT-100	Conseils de montage des cardans
BT-104	Soufflets et Triaxes FIAT
BT-105	Soufflets et Triaxes SEAT
BT-131	Refus des carcasses transmissions

APPLICATIONS

RENAULT		
MEGANE (95-02) (BA0/1_) - 1.4 e (BA0E, BA0V)	75 ch	01.1996 > 02.1999
MEGANE (95-02) (BA0/1_) - 1.4 Eco (BA0T)	71 ch	01.1996 > 03.1999
MEGANE (95-02) (BA0/1_) - 1.6 e (BA0F, BA0S)	90 ch	01.1996 > 03.1999
MEGANE (95-02) (BA0/1_) - 1.6 i (BA0L)	75 ch	01.1996 > 03.1999
MEGANE (95-02) (BA0/1_) - 1.9 D Eco (BA0U, SA0U, BA0A)	64 ch	01.1996 > 02.1999
MEGANE (95-02) (BA0/1_) - 1.9 dT (BA0K, SA0K, BA0Y, SA0Y)	90 ch	01.1996 >
MEGANE (95-02) (BA0/1_) - 2.0 i (BA0G)	114 ch	01.1996 > 12.1998
MEGANE (95-02) Cabriolet (EA0/1_) - 1.6 e (EA0F)	90 ch	10.1996 > 03.1999
MEGANE (95-02) Cabriolet (EA0/1_) - 2.0 (EA0G)	114 ch	04.1997 >
MEGANE (95-02) Cabriolet (EA0/1_) - 2.0 i (EA0G)	109 ch	03.1999 >
MEGANE (95-02) Classic (LA0/1_) - 1.4 (LA0E, LA0V)	75 ch	09.1996 > 02.1999
MEGANE (95-02) Classic (LA0/1_) - 1.6 e (LA0F, LA0S)	90 ch	09.1996 > 03.1999
MEGANE (95-02) Classic (LA0/1_) - 1.6 i (LA0L)	75 ch	09.1996 > 03.1999
MEGANE (95-02) Classic (LA0/1_) - 1.9 D (LA0A, LA0U)	64 ch	09.1996 > 02.1999
MEGANE (95-02) Classic (LA0/1_) - 1.9 dT (LA0K, LA0Y)	90 ch	09.1996 >
MEGANE (95-02) Classic (LA0/1_) - 2.0 i (LA07, LA0G)	114 ch	09.1996 > 12.1998
MEGANE (95-03) Coupé (DA0/1_) - 1.6 e (DA0F)	90 ch	03.1996 > 03.1999
MEGANE (95-03) Coupé (DA0/1_) - 2.0 i	109 ch	03.1999 > 08.2003
MEGANE (95-03) Coupé (DA0/1_) - 2.0 i (DA0G)	114 ch	03.1996 > 08.2003
MEGANE (95-03) Scenic (JA0/1_) - 1.4 i (JA0E)	75 ch	01.1997 > 12.1998
MEGANE (95-03) Scenic (JA0/1_) - 1.6 e (JA0F)	90 ch	01.1997 > 12.1998
MEGANE (95-03) Scenic (JA0/1_) - 1.6 i (JA0L)	75 ch	01.1997 > 12.1998

 Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.