


DONNEES TECHNIQUES

Compressed length [mm]	725
Uncompressed length [mm]	750
Number of splines (wheels side)	23
Number of Teeth, ABS ring	44
for vehicles with ABS	
ABS Ring Ø [mm]	85
(wheels side) shoulder Ø [mm]	57
ABS ring type	R
(wheels side) CV Joint Ø [mm]	84
Number of splines (gearbox side)	23
Without mounting pin (gearbox side)	

PHOTOS




DOCUMENTS

- BT-100** **Conseils de montage des cardans**
- BT-104** **Soufflets et Triaxes FIAT**
- BT-105** **Soufflets et Triaxes SEAT**
- BT-131** **Refus des carcasses transmissions**

APPLICATIONS

RENAULT		
CLIO (98-10) (BB__, CB__) - 1.5 dCi (BB08, CB08)	82 ch	06.2001 > 05.2005
KANGOO (97-07) (KC0/1_) - 1.5 dCi (KC08, KC09)	82 ch	07.2002 > 05.2005
KANGOO (97-07) (KC0/1_) - 1.9 dTi (KC0U)	80 ch	02.2000 >
KANGOO (97-07) Express (FC0/1_) - 1.5 dCi (FC07)	65 ch	12.2001 >
KANGOO (97-07) Express (FC0/1_) - 1.5 dCi (FC08, FC09)	82 ch	04.2003 >
KANGOO (97-07) Express (FC0/1_) - 1.9 D 65 (FC0E, FC02, FC0J, FC0N)	64 ch	08.1997 >

 Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.