

DONNEES TECHNIQUES

Compressed length [mm]	736
Number of splines (wheels side)	21
	for vehicles without ABS
(wheels side) shoulder Ø [mm]	50
(wheels side) CV Joint Ø [mm]	86
Number of splines (gearbox side)	23
(gearbox side) CV Joint Ø [mm]	70

PHOTOS




DOCUMENTS

BT-100	Conseils de montage des cardans
BT-104	Soufflets et Triaxes FIAT
BT-105	Soufflets et Triaxes SEAT
BT-131	Refus des carcasses transmissions

APPLICATIONS

RENAULT		
19 (88-92) (B/C53_) - 1.4	80 ch	01.1988 > 12.1992
19 (88-92) (B/C53_) - 1.4 (B532, C532) KAT	58 ch	01.1989 > 04.1992
19 (88-92) (B/C53_) - 1.4 (B53P, C53P)	58 ch	01.1989 > 12.1989
19 (88-92) (B/C53_) - 1.7 (B53B, C53B)	73 ch	09.1988 > 04.1992
19 (88-92) (B/C53_) - 1.7 (B53C, C53C)	90 ch	09.1988 > 04.1992
19 (88-92) (B/C53_) - 1.9 D (B534, C534, B53J, C53J)	64 ch	09.1988 > 04.1992
19 (88-92) Cabriolet (D53_) - 1.7	75 ch	07.1991 > 04.1992
	95 ch	07.1991 > 04.1992
19 (88-92) Chamade (L53_) - 1.4 (L532, L53P)	58 ch	07.1988 > 04.1992
19 (88-92) Chamade (L53_) - 1.7 (L53B)	73 ch	10.1989 > 04.1992
19 (88-92) Chamade (L53_) - 1.7 (L53C)	90 ch	07.1988 > 04.1992
19 (88-92) Chamade (L53_) - 1.7 (L53F)	107 ch	08.1988 > 12.1992
19 (88-92) Chamade (L53_) - 1.9 D (L534, L53J)	64 ch	10.1989 > 04.1992
19 (88-92) Société (S53_) - 1.9 D	65 ch	01.1988 > 12.1992
19 (92-02) (B/C53_) - 1.4	80 ch	01.1992 > 12.1995
19 (92-02) (B/C53_) - 1.4 (B532, C532)	58 ch	04.1992 > 12.1995
19 (92-02) (B/C53_) - 1.4 (B535, C535)	75 ch	01.1992 > 12.1995

RENAULT		
19 (92-02) (B/C53_) - 1.7 (B53B, C53B)	73 ch	04.1992 > 12.1995
19 (92-02) (B/C53_) - 1.7 (B53C, C53C)	90 ch	04.1992 > 12.1995
19 (92-02) (B/C53_) - 1.9 D (B53J, C53J)	64 ch	04.1992 > 12.1995
19 (92-02) Cabriolet (D53_, 853_) - 1.7 (D53C)	90 ch	04.1992 > 09.1993
19 (92-02) Chamade (L53_) - 1.7 (L53B)	73 ch	04.1992 > 12.1995
19 (92-02) Chamade (L53_) - 1.7 (L53C)	90 ch	04.1992 > 12.1995
19 (92-02) Chamade (L53_) - 1.9 D (L53J)	64 ch	04.1992 > 12.1995
19 (92-02) Société (S53_) - 1.9 D	65 ch	03.1992 > 12.1995

 Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.