

DONNEES TECHNIQUES

Length [mm]	595
Number of splines (wheels side)	25
	for vehicles without ABS
(wheels side) shoulder Ø [mm]	56
Position the retaining clip	Gearbox side
(wheels side) CV Joint Ø [mm]	90
Number of splines (gearbox side)	26
(gearbox side) CV Joint Ø [mm]	87
(gearbox side) shoulder Ø [mm]	40

PHOTOS




DOCUMENTS

BT-100	Conseils de montage des cardans
BT-104	Soufflets et Triaxes FIAT
BT-105	Soufflets et Triaxes SEAT
BT-131	Refus des carcasses transmissions

APPLICATIONS

FORD		
ESCORT 95 Courier (AVL) - 1.8 Turbo D	70 ch	12.1995 > 06.2001
ESCORT CLASSIC (AAL, ABL) - 1.8 TD	90 ch	10.1998 > 07.2000
ESCORT CLASSIC Turnier (ANL) - 1.8 TD	90 ch	02.1999 > 07.2000
ESCORT (90-92) (GAL) - 1.8 16V XR3i	105 ch	02.1992 > 12.1992
	130 ch	02.1992 > 12.1992
ESCORT (90-92) (GAL) - RS 2000	150 ch	05.1991 > 12.1992
ESCORT (90-92) Break (GAL, AVL) - 1.8 16V	105 ch	02.1992 > 12.1992
ESCORT (90-92) Cabriolet (ALL) - 1.8 16V XR3i	105 ch	02.1992 > 12.1992
	130 ch	02.1992 > 12.1992
ESCORT (92-95) (GAL) - 1.8 i 16V	105 ch	09.1992 > 01.1995
ESCORT (92-95) (GAL) - 1.8 TD	90 ch	02.1993 > 01.1995
ESCORT (92-95) (GAL) - 1.8 XR3i 16V 4x4	105 ch	08.1993 > 01.1995
	130 ch	08.1993 > 01.1995
ESCORT (92-95) (GAL) - RS 2000	150 ch	09.1992 > 01.1995
ESCORT (92-95) (GAL) - RS 2000 4x4	150 ch	08.1993 > 01.1995

FORD		
ESCORT (92-95) 3 volumes (GAL) - 1.8 TD	90 ch	08.1993 > 01.1995
ESCORT (95-00) (GAL, AAL, ABL) - 1.8 TD	90 ch	01.1995 > 10.1998
ESCORT (95-00) (GAL, AAL, ABL) - 1.8 Turbo D	70 ch	12.1995 > 10.1998
ESCORT (95-00) 3 volumes (GAL, AFL) - 1.8 TD	90 ch	01.1995 > 10.1998
ESCORT (95-00) 3 volumes (GAL, AFL) - 1.8 Turbo D	70 ch	12.1995 > 02.1999
ESCORT (95-00) Cabriolet (ALL) - 1.8 TD	90 ch	09.1995 > 08.1998
ESCORT (95-00) Cabriolet (ALL) - 1.8 Turbo D	70 ch	10.1996 > 08.1999
ESCORT (95-00) Clipper (GAL, ANL) - 1.8 TD	90 ch	01.1995 > 02.1999
ESCORT (95-00) Clipper (GAL, ANL) - 1.8 Turbo D	70 ch	12.1995 > 02.1999
ORION (90-93) (GAL) - 1.8 TD	90 ch	03.1992 > 12.1993

 Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.