


## DONNEES TECHNIQUES

Length [mm]	<b>555</b>
Number of splines (wheels side)	<b>28</b>
Number of Teeth, ABS ring	<b>50</b>
<b>for vehicles with ABS</b>	
(wheels side) shoulder Ø [mm]	<b>60</b>
ABS ring type	<b>R</b>
(wheels side) CV Joint Ø [mm]	<b>98</b>
Number of splines (gearbox side)	<b>27</b>
(gearbox side) CV Joint Ø [mm]	<b>85</b>

## PHOTOS



## DOCUMENTS

<b>BT-100</b>	<b>Conseils de montage des cardans</b>
<b>BT-104</b>	<b>Soufflets et Triaxes FIAT</b>
<b>BT-105</b>	<b>Soufflets et Triaxes SEAT</b>
<b>BT-131</b>	<b>Refus des carcasses transmissions</b>

## APPLICATIONS

<b>HONDA</b>		
ACCORD (93-97) (CC7, CD) - 2.0 i	116 ch	09.1993 > 01.1996
ACCORD (93-97) (CC7, CD) - 2.0 i S	131 ch	09.1993 > 01.1996
ACCORD (93-97) (CC7, CD) - 2.3 i SR	158 ch	09.1993 > 01.1996
ACCORD (93-97) Aerodeck (CE) - 2.0 i LS 16V (CE2)	136 ch	09.1993 > 02.1998
ACCORD (93-97) Aerodeck (CE) - 2.2 i ES (CE1)	150 ch	09.1993 > 02.1998
ACCORD (93-97) Coupe (CD7, CD9) - 2.0 (DC9)	136 ch	09.1993 > 12.1997
ACCORD (93-97) Coupe (CD7, CD9) - 2.2 i ES	150 ch	09.1993 > 02.1998

**⚠** Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.