

DONNEES TECHNIQUES

Length [mm]	596
Number of splines (wheels side)	26
Number of Teeth, ABS ring	50
for vehicles with ABS	
(wheels side) shoulder Ø [mm]	55
ABS ring type	R
(wheels side) CV Joint Ø [mm]	86
Number of splines (gearbox side)	27
(gearbox side) CV Joint Ø [mm]	85

PHOTOS



DOCUMENTS

BT-100	Conseils de montage des cardans
BT-104	Soufflets et Triaxes FIAT
BT-105	Soufflets et Triaxes SEAT
BT-131	Refus des carcasses transmissions

APPLICATIONS

HONDA		
CIVIC (92-95) (EG, EH) - 1.6 VTi (EG9)	160 ch	10.1991 > 11.1995
CIVIC (92-95) Coupe (EJ) - 1.6 i Vtec	160 ch	01.1994 > 11.1995
CIVIC (92-95) Hatchback (EG) - 1.6 VTi 16V (EG6)	160 ch	10.1991 > 11.1995
CIVIC (95-01) Hatchback (EJ9, EK1/3/4) - 1.6 VTi (EK4)	160 ch	11.1995 > 02.2001
CR-X (87-92) (ED, EE) - 1.6 i 16V Vtec (EE8)	150 ch	11.1991 > 02.1992
CR-X (92-98) (EH, EG) - 1.6 ESi (EH6)	125 ch	03.1992 > 11.1995

⚠ Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.